



Commercial Display Systems

17341 Sierra Highway Canyon Conutry CA 91351

Toll Free 800-478-3790 Local 818-361-8160 Canadian Toll Free 822-765-2361 Fax 818-361-8152

DEW POINT CHART

Non DOE Compliant Dew Point Chart

Normal Temperature Applications				Low Temperature Applications				
Glass Type	Ambient Temp F°	Case Temp F°	Relative Humidity		Glass Type	Ambient Temp F°	Case Temp F°	Relative Humidity
2 Pane No Heat Glass Package	75°	35°	63%		3 Pane Heated Glass Package	75°	-10°	68%
2 Pane Heated Glass Package	75°	35°	82%		3 Pane Heated Glass Package	75°	-5°	70%
					3 Pane Heated Gas Filled Glass Package	75°	-10°	75%

DOE Compliant Dew Point Chart

Normal Temperature Applications				Low Temperature Applications				
Glass Type	Ambient Temp F°	Case Temp F°	Relative Humidity		Glass Type	Ambient Temp F°	Case Temp F°	Relative Humidity
2 Pane Low E Gas Filled Glass Package	75°	35°	72%		3 Pane HH-1 Gas Filled Glass Package	75°	-10°	72%
3 Pane HH-1 Gas Filled Glass Package	75°	35°	82%		3 Pane HH-2 Gas Filled Glass Package	75°	-10°	82%

Relative humidity % is when condensation begins to form on glass
 The data presented on these charts can be affected by numerous conditions beyond the control of CDS. It is adviseable to be conservative when selecting doors from applications where moisture free glass is an absolute requirement.