

# Electrical Door Frame Specifications

Normal Temperature  
2024 Federal Specification

Advantage & Legacy Series  
No Heat Door Rail & Glass with Heated Frame Rail - Amps @ 115 Volts

Operating Conditions  
75°F amb/35°C case/68%RH

	Number Of Doors																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
2367	0.38	0.76	1.14	1.52	1.90	2.28	2.66	3.04	3.42	3.80	4.18	4.56	4.94	5.32	5.70	6.08	6.46	6.84	7.22	7.60
2373	0.38	0.76	1.14	1.52	1.90	2.28	2.66	3.04	3.42	3.80	4.18	4.56	4.94	5.32	5.70	6.08	6.46	6.84	7.22	7.60
2375	0.40	0.80	1.20	1.60	2.00	2.40	2.80	3.20	3.60	4.00	4.40	4.80	5.20	5.60	6.00	6.40	6.80	7.20	7.60	8.00
2379	0.39	0.78	1.17	1.56	1.95	2.34	2.73	3.12	3.51	3.90	4.29	4.68	5.07	5.46	5.85	6.24	6.63	7.02	7.41	7.80
2667	0.37	0.74	1.11	1.48	1.85	2.22	2.59	2.96	3.33	3.70	4.07	4.44	4.81	5.18	5.55	5.92	6.29	6.65	7.03	7.40
2673	0.40	0.80	1.20	1.60	2.00	2.40	2.80	3.20	3.60	4.00	4.40	4.80	5.20	5.60	6.00	6.40	6.80	7.20	7.60	8.00
2679	0.42	0.84	1.26	1.68	2.10	2.52	2.94	3.36	3.78	4.20	4.62	5.04	5.46	5.88	6.30	6.72	7.14	7.56	7.98	8.40
2867	0.39	0.78	1.17	1.56	1.95	2.34	2.73	3.12	3.51	3.90	4.29	4.68	5.07	5.46	5.85	6.24	6.63	7.02	7.41	7.80
2873	0.39	0.78	1.17	1.56	1.95	2.34	2.73	3.12	3.51	3.90	4.29	4.68	5.07	5.46	5.85	6.24	6.63	7.02	7.41	7.80
2875	0.46	0.92	1.38	1.84	2.30	2.76	3.22	3.68	4.14	4.60	5.06	5.52	5.98	6.44	6.90	7.36	7.82	8.28	8.74	9.20
2879	0.46	0.92	1.38	1.84	2.30	2.76	3.22	3.68	4.14	4.60	5.06	5.52	5.98	6.44	6.90	7.36	7.82	8.28	8.74	9.20
3067	0.41	0.82	1.23	1.64	2.05	2.46	2.87	3.28	3.69	4.10	4.51	4.92	5.33	5.74	6.15	6.56	6.97	7.38	7.79	8.20
3073	0.43	0.86	1.29	1.72	2.15	2.58	3.01	3.44	3.87	4.30	4.73	5.16	5.59	6.02	6.45	6.88	7.31	7.74	8.17	8.60
3075	0.43	0.86	1.29	1.72	2.15	2.58	3.01	3.44	3.87	4.30	4.73	5.16	5.59	6.02	6.45	6.88	7.31	7.74	8.17	8.60
3079	0.45	0.90	1.35	1.80	2.25	2.70	3.15	3.60	4.05	4.50	4.95	5.40	5.85	6.30	6.75	7.20	7.65	8.10	8.55	9.00

Low Temperature  
2024 Federal Specification \*\*\*

Advantage & Legacy Series  
Heated Door, & Frames Rails Non-Heated Glass Combined Amps @ 115 Volts

Operating Conditions  
75°F amb/-10°C case/55%RH\*\*\*

Series	Number Of Doors																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
2367	0.70	1.40	2.10	2.80	3.50	4.20	4.90	5.60	6.30	7.00	7.70	7.40	9.10	9.80	10.50	11.20	11.90	12.60	13.30	14.00
2373	0.68	1.36	2.04	2.72	3.40	4.08	4.76	5.44	6.12	6.80	7.48	8.16	8.84	9.52	10.20	10.88	11.56	12.24	12.92	13.60
2379	0.75	1.51	2.27	3.02	3.78	4.54	5.29	6.04	6.80	7.56	8.31	9.06	9.82	10.58	11.34	12.08	12.85	13.60	14.36	15.12
2667	0.78	1.56	2.34	3.12	3.90	4.68	5.46	6.24	7.02	7.80	8.56	9.36	10.14	10.92	11.70	12.48	13.26	14.04	14.82	15.60
2673	0.77	1.54	2.31	3.08	3.85	4.62	5.39	6.16	6.93	7.70	8.47	9.24	10.01	10.78	11.55	12.32	13.09	13.86	14.63	15.40
2679	0.82	1.64	2.46	3.28	4.10	4.92	5.74	6.56	7.38	8.20	9.02	9.84	10.66	11.48	12.30	13.12	13.94	14.76	15.58	16.40
2867	0.91	1.82	2.73	3.64	4.55	5.46	6.37	7.28	8.19	9.10	10.01	10.92	11.83	12.74	13.65	14.56	15.47	16.38	17.29	18.20
2873	0.86	1.72	2.56	3.42	4.28	5.14	6.00	6.86	7.72	8.60	9.46	10.32	11.18	12.04	12.90	13.76	14.62	15.48	16.34	17.20
2875	0.83	1.66	2.49	3.32	4.15	4.98	5.81	6.64	7.47	8.30	9.13	9.96	10.79	11.62	12.45	13.28	14.11	14.94	15.77	16.60
2879	0.92	1.84	2.77	3.69	4.61	5.54	6.46	7.38	8.30	9.22	10.15	11.07	11.99	12.91	13.83	14.76	15.68	16.60	17.52	18.44
3067	0.89	1.78	2.67	3.56	4.45	5.34	6.23	7.12	8.01	8.90	9.79	10.68	11.57	12.46	13.35	14.24	15.13	16.02	16.91	17.80
3073	0.96	1.92	2.88	3.84	4.80	5.76	6.72	7.68	8.64	9.60	10.56	11.52	12.48	13.44	14.40	15.36	16.32	17.28	18.24	19.20
3075	0.94	1.89	2.83	3.77	4.72	5.66	6.60	7.54	8.49	9.44	10.37	11.31	12.26	13.21	14.16	15.08	16.04	16.98	17.93	18.88
3079	0.91	1.82	2.73	3.64	4.55	5.46	6.37	7.28	8.19	9.10	10.01	10.92	11.83	12.74	13.65	14.56	15.47	16.38	17.29	18.20

**Note: For Low Temperature applications, the total "Amp Draw" must be considered using one "Circuit Breaker" due to the Anti-Condensation Controller controlling multiple frames in a line up.**

Note: Electrical Specification charts do not contain light amperages.  
Please refer to Electrical Lighting Specifications sheet for details.